



2D Long Range LED Barcode Scanner

Scan Depth up to 450 mm (17.7 in.), Detachable 1.8 m (6 ft.) USB-A Cable, 60 scans per Second, 100K Lux, Handheld, Rugged IP52-rated Housing, Black
SKU: 154116 | EAN-13: 0766623154116 | UPC: 766623154116

Dust-protected 1D / 2D USB Barcode Scanner that helps you improve Productivity in Retail, Hospitality, Warehousing, and Harsh Environments

The Manhattan 2D LED Barcode Scanner is your durable solution for streamlined data entry and enhanced efficiency to help improve routine transactions and automate paper-based processes. Capture barcodes from mobile devices, 1D and 2D Paper barcodes on items for sale, coupons, loyalty cards and more. This scanner is built for such different industries as retail/point-of-sale, healthcare, hospitality, warehousing or logistics.

Quick and Accurate Reads Every Time

With its wide scan field and scan depth of up to 450 mm (17.7 in.), it ensures quick and accurate reads every time. Significantly reduce errors and delays for seamless operations in your daily business.

Versatile Compatibility for Many Symbolologies

Equipped with advanced technology, it detects a wide range of popular 1D and 2D symbolologies, including UPC, EAN, QR Code, Data Matrix, PDF417, and many more. Whether it's barcodes or intricate QR codes, it handles it all with precision and speed.

Rugged Design for Harsh Environments

Featuring an IP52-rated housing, our scanner is built to withstand harsh environments with protection against dust and water ingress.

Reliable Performance in Any Lighting Condition

Experience maximum reliability even in the most challenging lighting conditions. With an exceptional ambient light tolerance of 100,000 lux, this scanner delivers reliable readings even in direct sunlight, ensuring uninterrupted workflow.

Plug-and-Play Installation for Effortless Setup

Experience hassle-free installation with easy plug-and-play functionality. No drivers or additional software required, simply connect the USB-A plug and start scanning. Compatible with Windows®, macOS®, Chrome OS™, and Linux®, it seamlessly integrates with your existing systems. Its wired USB connectivity ensures reliable performance without the hassle of changing batteries.

Enhanced Convenience with our Barcode Scanner Stand

For added convenience, pair our scanner with the Manhattan Barcode Scanner Stand #154192 for hands-free operation, ideal for busy retail environments and automated processes.

Features:

- Helps speed data entry, reduce errors and improve efficiency - ideal for retail transactions and automated processes
- Wide scan field providing quick, accurate reads up with a scan depth up to 450 mm (17.7 in.)

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Detects many popular 1D and 2D symbologies including UPC, EAN, QR Code, Data Matrix, PDF417, and many more
- IP52-rated housing to protect against dust and water in harsh environments
- ESD protection up to 16 kV (air) and 8 kV (contact)
- Highest ambient light tolerance of 100,000 lux for reliable readings even in direct sunlight conditions
- Keyboard wedge decoder that enables scanned data to be displayed as if directly entered from keyboard
- Detachable 1.8 m (6 ft.) cable with USB-A plug for reliable performance and no need to change batteries
- Easy plug-and-play installation; no drivers or other software required
- Compatible with Windows®, macOS®, Chrome OS™, and Linux®
- Ideal for use with Manhattan Barcode Scanner Stand #154192 for convenient, hands-free operation
- Three-year warranty

Specifications:

Standards and Certifications

- CE
- RoHS
- REACH
- UKCA
- FCC

General

- Supports 1D and 2D barcodes
- Scan light: LED
- Scan range (depth): 450 mm (17.7 in.)
- Scan rate: 60 scans per second
- Resolution
 - 1D: 3 mil/0.076 mm
 - 2D: 7 mil/0.18 mm
- Sensor size: 1280 (H) x 800 (V) pixels
- Field of view (FoV): Horizontal -45°, Vertical -36°
- Print Contrast Ratio (PCR): 20%
- Reading indicator: tone and LED
- Ambient light: 100,000 lux max. (sunlight)
- Drop resistance: 1.2 m (47.24 in.) on concrete surface
- MTBF: 50,000 hours
- Interface: USB-A
- Switch: trigger

Supported codes

- 1D symbologies: UPC-A, UPC-E, EAN-8/JAN-8, EAN-13/JAN-13, ISSN, UCC/EAN-128, Code 39, Code 39 Full ASCII, Code 128, Interleaved 25, Industrial 25, Matrix 25, Codabar/NW7, Code 93, Code11, China Post, MSI, Telepen, GS1 Databar Omni-directional, GS1 Databar Limited, GS1 Databar Expanded
- 2D symbologies: Aztec, Data Matrix, MaxiCode, QR Code, PDF417, Micro PDF417, HANXIN, MicroQR Code, Dotcode, Grid Matrix

Physical

- Dimensions (L x W x H): 172 x 67 x 87 mm (6.77 x 2.64 x 3.43 in.)
- Cable length: 1.8 m (6 ft.)
- Net weight: 220 g (0.49 lbs.)
- Gross weight: 300 g (0.66 lbs.)
- Housing: ABS, IP52-rated

Operating Environment

- Operation temperature: -10 - 50°C (14 - 122°F)
- Storage temperature: -20 - 70°C (-4 - 158°F)
- Humidity (non-condensing): 20 - 95% RH

Electrical

- Voltage: DC 5.0 V
- Current draw:
 - <130 mA (stand-by)
 - <280 mA (operation)

Package Contents

- 2D Long Range LED Barcode Scanner
- Instructions





Stand not included
Stand SKU: 154192